


269.00 EUR
incl. 19% VAT, plus [shipping](#)



- INTEL® Bay Trail SOC chipset
- Onboard INTEL® Bay Trail J1900/N2930 Quad Core processor
- Support DirectX 11 3D Graphics Acceleration
- Support DDR3L 1333
- Integrated HD Audio CODEC
- Support 2* INTEL® Gigabit LAN (WG82574L)
- Support 2*HDMI Ports
- Support 1*USB3.0 Port
- Support Power Onboard(wide voltage input 9~24V)
- Onboard 1*MiniPCI-E connector
- Onboard 1 *M- SATA connector
- 1 Phase CPU Power Support
- Support slim Fan design
- [NUC](#) Form Factor(101mm X101mm)

CPU/Chipset	<ul style="list-style-type: none"> INTEL® Bay Trail SOC chipset Onboard INTEL® Bay Trail J1900/N2930 Quad Core CPU
I.O Chipset	<ul style="list-style-type: none"> FINTEK F81803U
Memory	<ul style="list-style-type: none"> 1* SO-DIMM slot Support DDR3L 1333 Max. capacity of system memory up to 8GB
Expansion Slots	<ul style="list-style-type: none"> 1* Mini PCI-E connector (Half size)
Storage	<ul style="list-style-type: none"> 1* M-SATA Connector (Full size)
Audio	<ul style="list-style-type: none"> ALC887 Audio CODEC HD Audio CODEC / Spdif out
Ethernet LAN	<ul style="list-style-type: none"> 2* INTEL® WG82574L Chip PCI Express Gigabit LAN
USB	<ul style="list-style-type: none"> 4* USB 2.0 1* USB 3.0
Special Features	<ul style="list-style-type: none"> Support CPU Smart Fan Support Watch dog Technology Support Power On board Support slim Fan design Support 1*RS422/RS485/RS232 COM port Support Amplifier function(3W) All Tantalum Capacitor design All Power Pack MOSFET design
Back Panel I / O	<ul style="list-style-type: none"> 2* USB 2.0 ports 2* RJ-45 port 1* Line-out connector 2* HDMI ports 1* DC-Jack
Internal I / O	<ul style="list-style-type: none"> 1* USB 3.0 port 1* USB2.0 port 1* COM port 1* USB2.0 header 1* SATA2.0 1* 4Pin SATA Power connector
BIOS	<ul style="list-style-type: none"> AMI 64MB SMT Flash ROM
Form Factor	<ul style="list-style-type: none"> Thin mini ITX Form Factor(101mm X 101mm)