

919.00 EUR  
incl. 19% VAT, plus [shipping](#)



- INTEL® BayTrail--M N2930 SOC
- Onboard INTEL® BayTrail-M N2930 1.83GHz Quad Cores CPU
- Onboard SAMSUNG 4G/1333MHz DDR3L Memory
- Support DirectX 11 3D Graphics Acceleration
- Support 1\*Serial ATAll(3Gb/s) Devices
- Support Dual INTEL® Gigabit LAN
- Support CRT Output
- Equipped with 802.11 b/g/n WIFI card & External Antenna
- Support 3\* COM ports■COM2/COM3 Support RS422/485■
- Support 2.5" SATA HDD
- Support 1\*M-SATA Socket
- Support 1\*Mini PCI-E Socket
- Support 3\* USB2.0 Ports
- Support 1\* USB3.0 Port
- Support 3G SIM Card
- 37mm thin, slice design
- VESA mount(100mm X100mm &75mm x 75mm)

Panel	Panel Spec	AUO G121XN01.V0
	Viewable Size Image	12.1 inch With LED Backlight
	Active Area	245.76(H) x 184.32(V)
	Resolution	1024 x 768 @60Hz
	Display Color	262K
	Pixel Pitch	0.24 x 0.24 mm
	Aspect Ratio	4:3
	Contrast Ratio	700:1
	Max Brightness	500 cd/m <sup>2</sup>
	Viewing Angle(H/V)	H160/V160
	Response Time	25ms
	Temperature Range	-30 ~ +80°C (Operating)
	Touch	Touch panel style
Active Range		249.80 x 188.50mm ±0.2mm
Temperature Range		-10 ~ +60°C (Operating)
Transparency		80 ±3%
Surface Hardness		■ 3H (ASTM D3363, pressure 750g/45°)
Operating Force		■ 80g
Knock test		10,000,000 times keystrokes