



9999.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel Coffee Lake !
- Barebone !
- 12-36V DC-in !
- 4x HDMI / 2x DP !



- Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor (Max 35W)
- Intel® Coffee Lake-S H310 Chip
- Support Dual Channel DDR4 2133MHz up to 32GB
- Support MXM Type A/B VGA Card(Type A or B, Max 75W)
- 1* M.2 E key Support CNVi, 1* M.2 B key Support 3G/4G Module
- 2* RS232 (COM1/2 Support 5V/12V TTL), 4* USB3.1, 4* USB2.0, 1* GbE, 4* HDMI, 2* DP, 1* eDP (By MXM)
- 12~36V DC-in

MB Model	- JNC9AMXM-H310
Part No.	- HBJC909C9A
BIOS	- AMI 128MB SMT Flash ROM

CPU/Chipset	<ul style="list-style-type: none"> - Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor (Max 35W) - Intel® Coffee Lake-S H310 Chip
Memory	<ul style="list-style-type: none"> - 2* DDR42133MHz up to 32GB
Network	<ul style="list-style-type: none"> - 1* Intel® I219LM GbE
Storage	<ul style="list-style-type: none"> - 1* 2.5" SATA 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm) - 1* M.2 M Key Socket (2280, Support NVMe)
Rear Panel I/O	<ul style="list-style-type: none"> - 4* USB3.1 - 2* DP (Up: DP By CPU, Bottom: DP By MXM VGA Card) - 4* HDMI (2* EXT HDMI By MXM, INT HDMI2 BY MXM, INT HDMI1 By CPU) - 1* RJ45 - 1* RS232 - 1* Line-out, MIC - 1* DC Jack - 1* Power Button
Internal Connector	<ul style="list-style-type: none"> - 1* M.2 B Key Socket for 3G/4G Module - 1* M.2 E Key Socket for CNVi or PCI-E/USB WIFI/BT
Power Source	<ul style="list-style-type: none"> - DC 12~36V input
Compliance	<ul style="list-style-type: none"> - CE, FCC, RoHS, ErP Ready (Option)
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -10 ~ 50° C - Storage Temperature: -20 ~ 60° C
Dimensions	<ul style="list-style-type: none"> - 279.8 (W) x 224.0 (D) x 115.9 (H) mm
OS Support	<ul style="list-style-type: none"> - Windows 10, Linux