



999.00 EUR  
incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.5Ghz
- FANLESS carpc system
- Integr. Autostart Controller
- Dualchannel VGA

CARTFT.COM



**Support:** [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#) | [Dual-Out-HowTo \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.  
Celeron-M 1.7Ghz is recommended for fanless operation.

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller).

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

CALU specifications	
<b>Processor (supported)</b>	Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher
<b>Memory</b>	Supports DDR 333/266 DIMM RAM 0.8" low profile 2x memory slots ! Maximum : 2 GB
<b>Video</b>	Intel Extreme Graphics 2 Supports up to 64MB DVMT video memory
<b>Audio</b>	Software AC '97 Audio CODEC

<b>Peripheral Connection</b>	Front :  1 x IEEE 1394 Firewire port  1 x USB 2.0 / 1.1 Port  1 x MIC Port  1 x Ear Phone output Jack  Power-on button  Reset button  Power-on and HDD LED    Rear :  1 x RS232 COM port  1 x RJ45 10/100Mb Fast Ethernet  1 x Line-Out output Jack  2 x USB 2.0 / 1.1 Ports  1 x 15 pin VGA  1 x DVI
<b>Storage</b>	One 2.5 inch Hard Disk and 9.5mm high.  (Support Ultra DMA 33/66/100).
<b>Weight &amp; Size</b>	System approximately 3kg (fully equipped).  System Dimension: 155 x 255 x 55 mm
<b>Power req.</b>	9-16VDC, 5A

**Accessory**

<b>Storage</b>	Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo  Supports all 2.5" standard IDE hard drive, ATA-100/66/33.
<b>Scope of supply</b>	Connector cable for Plus, ignition plus and ground  Barebone  Barebone  CPU Kühlkörper

Installation Tutorial : [Support / Manuals](#)

Graphics driver for 800x480 resolution : [Here](#)